



**VASTR® Non-woven tape is a single-sided adhesive tape made from polypropylene nonwoven and coated with a VASTR® high performance adhesive layer with release liner. This makes VASTR® Non-woven tape suitable for bonding membranes to wood structures.**

### Application

VASTR® Non-woven tape should be used for wind and watertight sealing of non-woven membranes in facade and roof constructions. Both the permanent repair of damage, wind and watertight sealing of overlap seams and the connection of non-woven membranes such as Polytex® and TAFTEX® to structures should be processed with VASTR® Non-woven tape. VASTR® non-woven tape can be adhered directly to wood or steel substrates.

### Installation

VASTR® Non-woven tape must be applied to a dust and grease free, dry surface to ensure proper adhesion. Before applying VASTR® Non-woven tape, remove the release liner and apply the tape to the center of the seam / overlap. Press and rub the tape well to eliminate air bubbles and provide optimum permanent adhesion.

| Description           | Size         | Quantity     | Article no. | EAN code      |
|-----------------------|--------------|--------------|-------------|---------------|
| VASTR® Non-woven tape | 75 mm x 25 m | 8 roll / box | 8107502504  | 8714672005202 |

### Specifications

|  |  |
|--|--|
| Color<br><b>Gray</b>                                       | Adhesion on steel<br><b>38 N / 25 mm</b>   |
| Material<br><b>PP Non-woven</b>                            |  |
| Adhesive layer<br><b>Modified acrylic</b>                  | Protective coating<br><b>Release liner</b> |
| Storage<br><b>Dark, dry, 10 °C to 20 °C</b>                |  |
| Temperature resistance<br><b>-40 °C to + 80 °C, 120 °C</b> | Processing temperature<br><b>From 0 °C</b> |

